

# TECHNICAL DATASHEET

Update of the document : 07-02-18  
ISO reference : DON/LS 03.4238.A



LEMAITRE SECURITE SAS  
17 rue Bitschhoffen  
BP 90024

F 67350 La Walck FRANCE  
Tél. : +33 (0)3 88 72 28 80  
Fax : +33 (0)3 88 07 05 37

[www.lemaitre-securite.com](http://www.lemaitre-securite.com)  
[contact@lemaitre-securite.com](mailto:contact@lemaitre-securite.com)



## SNOWFOX S3 SRC

High shoe with fur lining in water-repellent grained leather

### PROTECTIONS FOR THIS MODEL



Sizes available from 35 to 47  
Weight of one pair in size 42 : 1000 gr.  
Certification  
N°0075/007/161/10/10/0461-EXT  
10/02/11  
Norm EN ISO 20345 : 2011

### Upper features

- Upper : water-repellent grained leather
- Collar : synthetic
- Tongue : synthetic
- Lining : synthetic fur
- Vamp lining : synthetic
- Backpart : synderm
- Eyelet : metallic
- Laces : polyamide
- Tongue marking : size, manufacturer, manufacture date (month, year), norm, protection, CE marking.

### Protections

- Toecap : polycarbonate (200 joules)
- Midsole : steel (1100 Newtons)

### Fitting features

- Lasting insole : textile
- Footbed : polyurethane

### Sole features

- Name : C07
- Material : dual density polyurethane
- Comfort sole density : 0,5
- Comfort sole color : dark grey
- Undermine sole density : 1
- Undermine sole color : black
- Slip resistance SRA (flat) : 0,40
- Slip resistance SRA (heel) : 0,40
- Slip resistance SRB (flat) : 0,17
- Slip resistance SRB (heel) : 0,13

### Advantages = End users benefits

- **2,2mm thickness leather** for better resistance (to abrasion and tearing) and longer durability.
- **Fur lining** for every work in cold conditions.
- **Non-metallic toecap made of injected polycarbonate** : invisible when worn as lightweight (2 times less than steel) and ergonomic, chemically inert, elastic (in a crash, the mouthpiece back into shape, releasing the foot easily), nonmagnetic (undetected by metal detectors) and thermal insulation (not sensitive to variation and heat transfer between -10 ° C to +40 ° C).
- **C07 sole** :
  - Attack heel, for a natural unfolding of the foot during walking and comfort while driving vehicle
  - Dual density polyurethane (PU / PU or PU2D) injected for better resistance and comfort
  - Heel shape for better security, especially when climbing ladders
  - Heel shock absorber
  - Non-slip structure with a studded open for better drainage of fluids

### Basics and additional requirements of the norm EN ISO 20345 : 2011

#### Toecap

steel polycarbonate aluminium HDFC Fiber composite

- (A)** Antistatic footwear.
- (P)** Penetration resistance.
- (Hro)** Resistance of the outsole to hot contact.
- (Wru)** Water penetration and water absorption resistant upper.
- (E)** Energy absorption of seat region.
- (Hi)** Heat insulation of sole complex.
- (M)** Metatarsal protection.

#### Anti-perforation insert

stainless steel composite (high tenacity fabric)

- (Fo)** Resistance of the outsole to fuel oil.
- (Ci)** Cold insulation of sole complex.
- (Wr)** Water resistant footwear.

Regarding the norm EN ISO 20345, the minimum results for slip resistance to get the SRC certificate are :  
SRA (flat) ≥ 0,32      SRB (flat) ≥ 0,18  
SRA (heel) ≥ 0,28      SRB (heel) ≥ 0,13

